

# Speedy Contour 270-K | Speedy Contour 270-KSL | Speedy Contour 320-K | Speedy Contour 320-KSL

## Deburring machine for Contours

The stationary edge- and contour milling machines are perfect for machining angular and round workpieces with plane inner- and outer contours. They are compact and handy tabletop machines finding their ideal use alongside CNC machines.



### Applications

- ▶ For precise deburring and chamfering of inner- and outer edges on flat workpieces
- ▶ Can be used for steel, hardened steel, aluminium, brass, copper, plastic, from soft plastic to acrylic glass, wood and much more
- ▶ Suitable for continuous operation





Further accessories can be found  
in our **Accessory Catalogue**.

### Professional advantages

- ▶ Ideal for chamfers up to 1 mm x 45°
- ▶ Suitable for processing small to medium-sized workpieces
- ▶ Low setup times with maximum flexibility
- ▶ Zero point clamping

### Features

- ✔ Easy operation
- ✔ Fast tool change
- ✔ Speed control (only with Speedy Contour 270-KSL and Speedy Contour 320-KSL)
- ✔ Chamfer angle can be changed due to contour cutter with different point angles

### Options

- ✔ Guide finger, radius- and chamfer cutter with guide ball bearing
- ✔ Attachment prism for processing of straight edges
- ✔ Slug remover set for face milling of cut-off rotary slugs up to max. Ø 1.5 mm
- ✔ Extraction socket
- ✔ Extraction device with automatic switch-on
- ✔ Special version for stainless steel processing

### Delivery contents

- ✔ Allen key 2.5 mm
- ✔ Cold-device cable
- ✔ Insert ring with borehole Ø 8 mm
- ✔ Operating manual

### Technical data

	Speedy Contour 270-K	Speedy Contour 270-KSL	Speedy Contour 320-K	Speedy Contour 320-KSL
Motor	0.14 kW 21,000 rpm	0.14 kW 12,000-32,000 rpm	0.14 kW 21,000 rpm	0.14 kW 12,000-32,000 rpm
Energy	230 V, 50 Hz	230 V, 50 Hz	230 V, 50 Hz	230 V, 50 Hz
Maximum chamfer width	2 mm	2 mm	2 mm	2 mm
Guide ball bearing	min. Ø 3 mm	min. Ø 3 mm	min. Ø 3 mm	min. Ø 3 mm
Dimensions (LxWxH)	270 × 170 × 120 mm	270 × 170 × 130 mm	320 × 200 × 140 mm	320 × 200 × 140 mm
Weight	8.6 kg	9 kg	12 kg	13 kg
Item no.	1011	1053	961	938